

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder x Reservoir	1.8	18	16 in.·lbf
Master cylinder x Brake booster	13	130	9
Master cylinder piston stopper bolt	10	100	7
Brake line union nut	15	155	11
Brake booster clevis lock nut	25	255	18
Brake booster x Pedal bracket	13	130	9
Brake booster push rod	7.4	75	65 in.·lbf
Bleeder plug	11	110	8
Brake caliper	8.3	85	74 in.·lbf
Brake actuator	42	425	31
Brake pedal x Pedal bracket	118	1,200	87
Front disc brake caliper x Steering knuckle	39	400	29
Front disc brake caliper x Flexible hose	5.4	55	48 in.·lbf
Front disc set screw	104	1,065	77
Rear disc brake torque plate x Rear axle carrier	39	400	29
Rear disc brake caliper x Flexible hose	34	350	25
Rear disc brake caliper installation bolt	5.4	55	48 in.·lbf
Rear disc set screw	13	130	9
Parking brake pedal bracket x Body	32	330	24
Parking brake pedal bracket x Parking brake pedal (LHD)	5.4	55	48 in.·lbf
Parking brake release lever x Lower pad	5.4	55	48 in.·lbf
Brake actuator x Actuator bracket	19	195	14
Actuator bracket x Body	7.8	80	69 in.·lbf
Front speed sensor installation bolt	7.8	80	69 in.·lbf
Rear speed sensor installation bolt	5.5	56	49 in.·lbf
Speed sensor harness clamp bolt			